

World Best Card Printer



HODOO

Advanced Digital Convergence


DESIGNED FOR

TELECOM PROVIDERS BANKS CREDIT INSTITUTIONS GOVERNMENTS
CLUBS / ASSOCIATIONS PETROLEUM COMPANIES INSURANCE COMPANIES
SERVICE BUREAUX LOTTERIES AMUSEMENT PARKS RETAIL BUSINESS


Smallest and Strong Functions



NO JAM



Folder Hopper



**Free for Card
Thickness**



Easy To Upgrade

HODOO Technical Features

► Printer

Mode	Color dye sublimation and mono thermal transfer
Performance	SIP-30 1,200CPH(Mono), 150CPH(Color) SIP-30F 130CPH(YMCKOK)
Resolution	300DPI
Input Hopper	100 cards / Folder type
Output Hopper	50 cards
Card Dimensions	ISO CR-80 standard
Card Thickness	From 0,25mm to 1,6mm (from 10mil to 64mil)
Card material	PVC, PVC composite
Bar Codes	Code 39, EAN 8, EAN 13, Code 128 and others
Memory	16MB RAM, FLASH 8MB
CPU	32Bit Processor
► Display	
LCD Panel	2,0" color lcd
LED	3 LEDs (Green, Red, Yellow)
Button	2 Button for feed and reset in jam
► Option	
Magnetic Stripe	Tracks 1,2,3 ISO 7811, LOCO/HICO, NTT
Chip	Chip contact initializing, PCSC or Serial
SAM Socket	PLCC type 2ea and SIM type 4ea
RF	13,56MHz ISO 14443 type A/B, MIFARE®
Large Hopper	150/500 cards input/output hopper
► Software	
Driver	Unix, Linux, Windows(2000, 2003, XP, Vista, 7-32bits or 64bits)
Firmware	Auto download
Security	Security HSM Approval Encryption & Decryption Security Module(DES, 3DES methods) Security Commands for lock/unlock
► Case	
Interface	USB, Serial, TCP / IP (option)
Power Supply	100V - 240V, 50 - 60Hz
Dimensions (DxWxH)	SIP-30 174 x 280 x 166 mm, 4,5kg SIP-30F 174 x 395 x 166 mm, 6,4kg



Text



Image



Barcode



Magnetic



Chip



RF

MODEL **HODOO SIP-30**



MODEL **HODOO SIP-30F**
[Flipover]



*Data subject to change without notice.